



OILENCE
Oil & Gas Supply

Product: HD3840UA (Rotational Moulding)

High Density Polyethylene

Typical properties	Test Method(ASTM)	Unit	Value
MFI@190°C, 2.16 kg	D-1238	gr/10min	3.8 - 4.5
Density	D-1505	gr/cm ³	0.935-0.939
Tensile Strength@Yield	D-638	Mpa	18
Tensile Modulus	D-638	Mpa	-
Elongation@Break	D-638	%	1000
Flexural Modulus	D-790	Mpa	700
Hardness Shore D	D-2240	-	-
Charpy Impact Resistance (Notch)	D-256	Kj/m ²	20

Values shown are averages & are not to be considered as product specifications.

Main application & Characteristics:

HD3840UA is a linear, UV stabilized virgin medium density polyethylene copolymer grade (MDPE), with a narrow molecular weight distribution.

Characteristics:

- High stiffness.
- Good impact stress.
- Whiteness.
- UV stabilized.
- Good Stress Cracking Resistance.
- Excellent process-ability.
- Excellent internal and external surface finish.

Typical applications are:

- Rotational moulded items with good stiffness, such as: Septic tanks and Ordinary containers.
- Injection moulded technical parts and closure.


* **HD3840UA is suitable for food contact.**

29th Floor, Al Saqer Business Tower, Sheikh Zayed Road, Dubai, UAE

 (+971) 45281400

 (+971) 557413294

 info@oilence.com

 www.oilence.com



HANiS